






















FLOOR DRAINS WITH NEPTUNE FLOAT



FLOOR DRAIN WITH SIDE OUTLET DN50 WITH A COLLAR AND PLASTIC/STAINLESS STEEL FRAME

If the water level drops, the NEPTUNE float will close the outlet to prevent the back flow of odour from the sewage line. Made of PP, PS and stainless steel DIN 1.4301. Load capacity K3 (300 kg). Temperature resistance up to 70°C. Tested in compliance with EN 1253.

💧 Flow rate (NEPTUNE float): 26-52 l/min

		PART NUMBER NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	STAINLESS STEEL FRAME
 		L1 425 X L L1PVB 50 X L	8/192	0,58	-
		L1 425 N X L L1PVB 50 N X L	8/192	0,60	✓
 		F1 425 X L F1PVB 50 X L	8/192	0,58	-
		F1 425 N X L F1PVB 50 N X L	8/192	0,60	✓
 		G1 425 X L G1PVB 50 X L	8/192	0,58	-
		G1 425 N X L G1PVB 50 N X L	8/192	0,60	✓
 		425 X L PVB 50 X L2	8/192	0,59	-
		425 N X L PVB 50 X N L2	8/192	0,60	✓
 		445 X L PVB 50 X L4	8/192	0,71	✓
 		C 425 X L CPVB 50 X L	4/168	0,61	✓
Type S		S 425 X L SPVB 50 X L	4/168	0,75	✓
 		C1 425 X L C1PVB 50 X L	4/168	0,75	✓
Type S1		S1 425 X L S1PVB 50 X L	4/168	0,92	✓